



Datasheet

High Bay Linear Light Available in 600K Cool White

The LED High Bay Linear range of Prolite fittings are highly energy efficient with a high lumen output. Designed for use in industrial applications including warehouses and cold storage units these fittings have excellent heat dissipation, are IP65 and IK10 rated and supported by a 5 year warranty. The fittings use high quality LED chips and drivers and are UV, IR and Mercury Free. With typical return on investment in only 3 years the LED High Bay Linear range is a fantastic LED upgrade solution for many industrial applications with additional sensor options also available to achieve additional energy savings.



Specification

- 130Lm/w
- Input Voltage 100-277V AC, 50-60HZ
- Colour Temperature 6000K
- IP65 rated
- IK10 rated
- Beam angle 120 degrees
- CRI >80

Additional Options

- Sensor
- Remote control for Sensors
- Surface Mount Kit



RoHS



| Product Code | Description | Wattage | Lumens | Dimensions |
|---------------------|--|---------|---------|---------------|
| LED/HBL/150W/6K/DIM | LED High Bay Linear 150w 0-10v Dimmable 6000k | 150w | 19500lm | 905x135x72mm |
| LED/HBL/200W/6K/DIM | LED High Bay Linear 200w 0-10v Dimmable 6000k | 200w | 26000lm | 1205x135x72mm |
| LEDHBL/SENSOR | Microwave Sensor for LED High Bay Linear Fittings | - | - | - |
| LEDHBL/REMOTE | Remote Control for LEDHBL/SENSOR | - | - | - |
| LEDHBL/SURFACEKIT | Surface Mount Kit for LED High Bay Linear Fittings | - | - | - |

For more information call the sales team on **01780 758590**