

T8 LED Tube

Available in a Range of Colour Temperatures



Low Energy Replacement for the T8 Fluorescent Tube

Key Features

- Adjustable rotating end caps for lamp holder adjustment
- Single end power input for increased efficiency and safety
- Opal polycarbonate shatterproof cover
- Input voltage: 85-265V 50/60Hz
- Colour temperature CDL 5500-6500K (2700-3500K, 4000-4500K available upon request)
- Operating temperature range 0°C - 45°C
- Storage temperature range 30°C - 65°C
- Power factor ≥ 0.9
- Power efficiency > 85%
- Beam Angle 120°
- LED Type: SMD
- CRI 70 ($\pm 10\%$)
- Light efficiency 100-110 Lm/W



Product Code	Length	Consumption	Lumens
T8L/2FT/8W/CDL/VDE	2ft / 600mm	8W	850 lm $\pm 10\%$
T8L/4FT/18W/CDL/VDE	4ft / 1200mm	18W	2160 lm $\pm 10\%$
T8L/5FT/24W/CDL/VDE	5ft / 1500mm	24W	2880 lm $\pm 10\%$
T8L/6FT/28W/CDL/VDE	6ft / 1800mm	28W	3360 lm $\pm 10\%$
T8L/8FT/40W/CDL	8ft / 2400mm	40W	4800 lm $\pm 10\%$

For more information call the sales team on **01780 758590**