




## Product Information Sheet

In accordance with schedule 8 of the Ecodesign for Energy-Related Products and Energy Information (Lighting Products) Regulations 2021

Supplier's name or trade mark: Prolite Lamps			
Supplier's address: Meadow Park, Bourne Road, Essendine, Stamford, PE9 4LT			
Model Identifier: GOLF/1.5W/BC/6000K & GOLF/1.5W/ES/6000K			
Type of light source: LED Polycarbonate Golf Balls			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	B22 & E27		
Mains or non-mains:	MLS	Connected light source (CLS)	N/A
Colour-turnable light source:	N/A	Envelope:	no
High luminance light source:	N/A		
Anti-glare shield:	N/A	Dimmable:	No
Product parameters			
Parameter	Value	Parameter	Value
General product parameters			
Energy consumption in on-mode (kWh/1.000 h) rounded up to the nearest integer	1.5	Energy efficiency class	G
Useful luminous flux ( $\Phi_{use}$ , indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	100 in sphere (360°)	Correlated colour temperature, rounded to the nearest 100K, that can be set	6000K
On-mode power ( $P_{on}$ ), expressed in W and rounded to the second decimal point	1.5	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal point	0

Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal point	0		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	70	Spectral power distribution in the range 250 nm to 80nm, at full-load	
	Width	45		
	Depth	45		
Claim of equivalent power see paragraph [2(1) and (2)]	N/A		If yes, equivalent power (W)	
			Chromacity coordinates (x and y)	0.32 0.34
Parameters for directional light sources:				
Peak luminous intensity (cd)	N/A		Beam angle in degrees, or the range of beam angles that can be set	N/A
Parameters for directional light sources:				
R9 colour rendering index vaue	0		Survival factor	0.9
The lumen maintenance factor	0.93			
Parameters for LED and OLED mains light sources:				
Displacement factor (cos φ1)	0.5		Colour consistency in McAdam ellipses	6
Claims that and LED light source replaces a fluorescent light source without integrated ballast of a particular wattage (see paragraph [2(3)]).	N/A		If yes then replacement claim (W)	
Flicker metric (Pst LM)	0.9		Stroboscopic effect metric (SVM)	0.4