




Product Information Sheet

In accordance with schedule 8 of the Ecodesign for Energy-Related Products and Energy Information (Lighting Products) Regulations 2021

Supplier's name or trade mark: Prolite Lamps			
Supplier's address: Meadow Park, Bourne Road, Essendine, Stamford, PE9 4LT			
Model Identifier: PAR38/LED/15W/ES/3K			
Type of light source: PAR38 15W IP65 Dimmable LED Reflector Lamp			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS)	N/A
Colour-turnable light source:	N/A	Envelope:	No
High luminance light source:	No		
Anti-glare shield:	N/A	Dimmable:	Yes
Product parameters			
Parameter	Value	Parameter	Value
General product parameters			
Energy consumption in on-mode (kWh/1.000 h) rounded up to the nearest integer	15	Energy efficiency class	F
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1100 in a wide cone (120°)	Correlated colour temperature, rounded to the nearest 100K, that can be set	3000K
On-mode power (P_{on}), expressed in W and rounded to the second decimal point	15	Standby power (P_{sb}), expressed in W and rounded to the second decimal point	0



Product Information Sheet

Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal point	0		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lightng control parts and non-lighting control parts, if any (millimetre)	Height	135	Spectral power distribution in the range 250 nm to 80nm, at full-load	
	Width	123		
	Depth	123		
Claim of equivalent power see paragraph [2(1) and (2)]	Yes		If yes, equivalent power (W)	35
			Chromaticity coordinates (x and y)	0.434 0.4
Parameters for directional light sources:				
Peak luminous intensity (cd)	N/A		Beam angle in degrees, or the range of beam angles that can be set	55
Parameters for directional light sources:				
R9 colour rendering index vaue	6		Survival factor	0.9
The lumen maintenance factor	0.96			
Parameters for LED and OLED mains light sources:				
Displacement factor (cos ϕ1)	N/A		Colour consistency in McAdam ellipses	N/A
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage (see paragraph [2(3)]).	N/A		If yes then replacement claim (W)	
Flicker metric (Pst LM)	1		Stroboscopic effect metric (SVM)	0.7